

SMART



People
Choice
Start

ECO LAB

Simplicity is GENIUS



Semi Automated Clinical Chemistry Analyser

- Robust and reliable diagnostics solution
- Consistent performance and easy operation

Technical Specifications

PHOTOMETRIC MODULE

- Seven Narrowband Interference Filters
- Filter Wavelengths: 340, 405, 505, 546, 578, 630 and 670nm (1 open position for optional filter)
- IAD process ensures long filter life
- Wavelength Accuracy: ± 2 nm
- Silicon Photo Diode detector
- Absorbance Range: 0.0–3.0 A
- Resolution: 0.0001 Absorbance Units
- Photometric Drift: < 5 mAbs/30min
- CV: $< 1\%$

TEMPERATURE OF FLOW CELL/CUVETTE

- 25°C, 30°C, 37°C
- Temperature Stability: $\pm 0.2^\circ\text{C}$

DISPLAY

- 5.7 Inch LCD display screen
- High Contrast Display

KEYBOARD

- Tactile touch QWERTY keypad
- Visual indication on keypad during aspiration

PRINTER

- Internal 80mm thermal printer with full graphics printing

MEASURING MODULE

- Dual mode (Flow cell & Cuvette)
- High quality Quartz flow cell for precise measurements
- 30 μl Flowcell volume
- Peltier-controlled reaction temperature
- External cuvettes (10mm path length)

REACTION VOLUME

- Minimum aspiration volume - 300 μl
- Maximum aspiration volume - 5ml

DIMENSIONS

- Length : 422mm
- Width : 324mm
- Height : 176mm
- Weight : 6.5 kg

ISO 9001-2015 certified

ANALYSIS METHOD

- Endpoint, Fixed time and Kinetic
- Sample blanking and Reagent Blanking
- Direct Absorbance measurement mode

TEST PROFILES

- User defined 10 Test Profiles
- 10 tests can be added in each profile

TEST CHANNELS

- 48 dedicated assays
- Direct access keys for dedicated assays
- Open channel capability
- 200 programmable channels

DATA MANAGEMENT

- Storage of up to 10,000 test results
- Stores 30 days QC for each Assay
- Reagent Blank storage

REPORTS

- Search by date, sample ID or Test Name
- Calibration Reports, QC results

UNITS

- 15 pre-defined measurement units

QC AND CALIBRATION

- Daily and monthly QC with data archiving.

INTERFACE

- RS 232 Port • USB Port
- PC Connectivity (optional)

POWER

- Input Voltage Range : 88 - 264 VAC
- Frequency Range : 47 - 63 Hz
- Power consumption : 75 W max



Marketed & Distributed by (OEM Based) :

JK BIOMED
(A JK GROUP OF COMPANY)

H.O. # 157, 1st Floor, 12th Main Nagendra Block, BSK 3rd Stage Bangalore - 560050.

B.O. # 55/1, 1st Floor, 2nd Main, 6th Cross Byatarayanapura, Bangalore - 560026.

Ph. : 080-26725522, 26758990, Mob. : 099020 02455

Mail ID : info@jkbiomed.com, varadharajan@jkbiomed.com